Growth and Characterization of GaN As(P) for High Efficiency Solar Cells

Final Subcontract Report 29 July 1999–28 September 2003

V. Narayanamurti
Harvard University
Cambridge, Massachusetts



Operated for the U.S. Department of Energy Office of Energy Efficiency and Renewable Energy by Midwest Research Institute • Battelle

Contract No. DE-AC36-99-GO10337

Growth and Characterization of GaN As(P) for High Efficiency Solar Cells

Final Subcontract Report 29 July 1999–28 September 2003

V. Narayanamurti
Harvard University
Cambridge, Massachusetts

NREL Technical Monitor: R. Matson

Prepared under Subcontract No. AAD-9-18668-17



Operated for the U.S. Department of Energy Office of Energy Efficiency and Renewable Energy by Midwest Research Institute • Battelle

Contract No. DE-AC36-99-GO10337

This publication was reproduced from the best available copy Submitted by the subcontractor and received no editorial review at NREL

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or any agency thereof.

Available electronically at http://www.osti.gov/bridge

Available for a processing fee to U.S. Department of Energy and its contractors, in paper, from:

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062

phone: 865.576.8401 fax: 865.576.5728

email: mailto:reports@adonis.osti.gov

Available for sale to the public, in paper, from:

U.S. Department of Commerce National Technical Information Service 5285 Port Royal Road

Springfield, VA 22161 phone: 800.553.6847 fax: 703.605.6900

email: orders@ntis.fedworld.gov

online ordering: http://www.ntis.gov/ordering.htm



Table of Contents

Abstract1						
Project Objective						
Accomplishments 1						
Summary5						
References6						
List of Figures						
Figure 1. (left) Room temperature BEEM spectra of $GaAs_{1-x}N_x$ for seven different nitrogen compositions; (right) second derivative (SD) BEEM spectra. The inset shows the ratio of the Γ -like peak to the L-like peak as a function of nitrogen content.						
Figure 2. (left) Band structure for GaP. Note, the material is an indirect gap semiconductor and the conduction band minimum occurs at the X-point. (right) BEEM spectra for six different nitrogen compositions in GaN _x P _{1-x} 3						
Figure 3. Schematic of a possible ordering of the X, L, and Γ valleys in pure GaP against GaP:N system under dilute N compositions						

Abstract

Scanning Tunneling Microscopy (STM) and Ballistic Electron Emission Microscopy (BEEM) have been used to characterize GaN_xAs_{1-x} and GaN_xP_{1-x} as a function of composition. The reduction in band gap has been measured. Detailed studies of the band structure as a function of N composition has led to a basic understanding of the materials system. The major results of this work include: (i) determination of relative contributions of the Γ - and L-like bands of GaN_xAs_{1-x} to the BEEM spectra; (ii) determination of the composition dependence of the Au/ Γ - and L-like bands of GaN_xAs_{1-x} Schottky barrier height; (iii) development of a model to describe the BEEM results at nonepitaxial metal/semiconductor interfaces; and (iv) ballistic electron emission spectroscopy studies of of GaN_xP_{1-x} samples which demonstrated possible splitting in the degeneracy of the X valley due to the nitrogen. The data were qualitatively described by the recent perturbed host states model of Kent and Zunger.

Project Objective


To characterize $GaAs_{1-x}N_x$ and $GaP_{1-x}N_x$ alloys using STM/BEEM. To understand the origins of the giant band gap bowing of these compound semiconductor alloys as a function of nitrogen concentration.

Accomplishments

The funding provided through the sub-award from the University of California at Santa Barbara has led to the following significant accomplishments:

- 1. The STM/BEEM technique has been developed to a high degree of perfection for studying the Schottky barriers and band structure of a range of compound semiconductor alloys that have been of interest to NREL for many years because of their potential applications to solar cells. The technique was perfected through initial studies of the prototypical alloy system Ga_xAl_{1-x}As where the band structure is well known¹ through other spectroscopic techniques. Two major reviews^{2, 3} highlight how this technique can be used for such studies.
- 2. Having developed a basic understanding of the BEEM technique and its capabilities for studying the band structure, we began a systematic investigation of GaA_{1-x}N_x alloys grown by Molecular Beam Epitaxy (MBE) by Professor Charles Tu at UCSD. During the 2000-2001 time frame we made a series of BEEM measurements of such structures⁴ ranging in composition from x=0.003 to x=0.02; that is, nearly an order of magnitude. The BEEM spectra clearly showed bands that evolve markedly as a function of nitrogen concentration. Two peaks that could be identified as Γ and L bands were observed, as shown in Fig. 1 for the room temperature BEEM spectra. As the nitrogen concentration increased, the energetic separation between these peaks was found to increase and with a decrease in the

relative contribution of the L band. The Schottky barrier for the Au/GaAsN was found to decrease markedly with nitrogen concentration. The observed Schottky barrier reduction followed the decrease in the Γ - band.







Figure 1 (left) Room temperature BEEM spectra of $GaAs_{1-x}N_x$ for seven different nitrogen compositions; (right) second derivative (SD) BEEM spectra. The inset shows the ratio of the Γ-like peak to the L-like peak as a function of nitrogen content.

A particularly interesting feature of the BEEM data was the observation of a weaker 3^{rd} band for X=0.012 and 0.017 and placed approximately $\sim\!\!0.40~_eV$ above the Γ band. The BEEM data are the only means to observe such effects and have been interpreted as a splitting of the four-fold L valley into the $a.(L_{1c})$ singlet and $t_2(L_{1c})$ triplet states. The BEEM results also provided strong evidence for a model of nitrogen induced Γ -L mixing as an explanation for the giant band gap reduction in such alloys.

3. Having developed a basic understanding of GaAsN we explored the comparison case of GaN_xP_{1-x}. This is a particularly interesting case because GaP is an indirect bandgap semiconductor (see the left panel of Fig. 2 for the GaP band structure) as distinct from the direct bandgap material GaAs. The evolution of the band structure⁵ was again studied as a function of nitrogen composition. Typical BEEM spectra are shown in the right panel of Fig. 2. Considerable structure was observed with the dominant X band being the lowest state and moving downwards in energy by as much as 300 meV for 3% N. Additional fine structure was interpreted as a splitting in the degeneracy of the X-valley due to the perturbation in the GaP lattice by nitrogen alloying.






Figure 2 (left) Band structure for GaP. Note, the material is an indirect gap semiconductor and the conduction band minimum occurs at the X-point.

(right) BEEM spectra for six different nitrogen compositions in GaN_xP_{1-x}. Note the downward motion of the X band with increasing nitrogen content. Additionally, note the correspondence of the BEEM peak positions and the band positions shown on the left.

The perturbed states were qualitatively compared with the theory of Kent and Zunger⁶. The ordering of the primary conduction band X_{1c} , X_{3c} , L_{1c} , and Γ_{1c} of states of GaP are shown on the left hand side of Fig. 3. The nitrogen derived states, $a_1(N)$, $a_1(X)$, ... etc., are shown in the right hand side of Figure 3.




Figure 3 Schematic of a possible ordering of the X, L, and Γ valleys in pure GaP against GaP:N system under dilute N compositions. Considering the large scattering in the reported values for the relative position of the X_{3c} valley, the possibility for the intermixing of X_{3c} and L_{1c} valleys is not ruled out.

- 4. The BEEM measurements provide a unique and important compliment to optical studies. The selection rules for BEEM are different and allow one to see both direct and indirect dimensions. Combining BEEM with optics would therefore be important to do. We have recently succeeded in seeing BEEM luminescence⁷ from GaAs samples and we can now begin to study simultaneously transport and optical properties.
- 5. We developed an interface scattering model to describe BEEM results from nonepitaxial metal/semiconductor interfaces. The model starts with a Hamiltonian consisting of the sum of two terms: one term, H_0 which describes an ideal interface for which the interface parallel component of wave vector is a good quantum number, and the second term, δH which describes interfacial scattering centers. The eigenstates of H₀ consist of an incident and a reflected part in the metal and a transmitted part in the semiconductor. The three components of each eigenstate have the same interface parallel wave vector. Because tunneling preferentially weights forward-directed states, the interface parallel component of wave vector is small for the H₀ eigenstates that are initially populated with high probability in BEEM. δH scatters electrons between the eigenstates of H₀. The scattering conserves energy, but not the interface parallel wave vector. In the final state of the scattering process, states with a large interface parallel wave vector can be occupied with reasonable probability. If scattering is weak, so that the parallel wave vector is nearly conserved, the calculated collector current into conductionband valleys with zero parallel wave vector at the minimum, such as the Γ valley for GaAs (100), is much larger than the calculated collector current into

conduction-band valleys with a large parallel wave vector at the minimum, such as the L valleys for GaAs (100). However, if scattering is strong, the injected electron flux distribution is redistributed and valleys with zero interface transverse wave vector at their energy minimum are not preferentially weighted. Instead, the weighting varies as the density of final states for the scattering process so that, for example, the calculated L-channel collector current is much larger than the calculated G-channel collector current for GaAs (100). Interfacial scattering reduces the overall magnitude of the calculated BEEM current near threshold for GaAs. We generalize the model to describe buried heterostructures and apply it to the Au/GaAs (100) interface and GaAs/Al_xGa_{1-x}As heterostructures buried beneath this interface. Experimental results on these materials are presented and compared with the model. Strong scattering is required to describe the observed BEEM currents for Au/GaAs (100) and buried GaAs/ Al_xGa_{1-x}As heterostructures.

Summary

As a result of the studies initiated through the GaNAs characterization project, we have:

- 1) established BEEM/STM as a powerful probe of the band structure of compound semiconductor alloys in general;
- 2) we have shown the value of this technique in providing a detailed understanding of the giant bandgap reduction for the specific cases of nitrogen doped compound semiconductors (GaAs and GaP).

References

- 1. "Second Derivative Ballistic Electron Emission Spectrocopy in Au/(AlGa)As," M. Kozhevnikov, V. Narayanamurti, D.L. Smith, Yi-Jen Chiu, *Materials Research Society Symp. Proc.* **584**, 207 (2000)
- 2. "The role of BEEM for characterization of physical phenomena in semiconductors alloys and quantum structures," V. Narayanamurti and M. Kozhevnikov, Invited Review Paper, *International Journal of High Speed Electronics and Systems* **10**, 55 (2000).
- 3. "BEEM imaging and spectroscopy of buried structures in semiconductors," V. Narayanamurti and M. Kozhevnikov, *Physics Reports*, **34916**, 447-514, (2001)
- 4. "Evolution of GaAs_{1-x}N_x conduction states and giant Au/ GaAs_{1-x}N_x Schottky barrier reduction studied by ballistic electron emission spectroscopy," M. Kozhevnikov, V. Narayanamurti, C.V. Reddy, H.P. Xin, C.W. Tu, A. Mascarenhas, and Y. Zhang, *Phys. Rev. B Rapid Communication* **61**, R7861 (2000-II).
- 5. "Evolution of the GaN_xP_{1-x} alloy band structure: A ballistic electron emission spectroscopic investigation," C.V. Reddy, R.E. Martinez II, V. Narayanamurti, *Physical Review B*, Vol. **66**, 235313 (2002)
- 6. P.R.C. Kent and A. Zunger, Phys. Rev. B. **64**, 115208 (2001)
- 7. "Room-Temperature Ballistic Electron Emission Luminescence Spectroscopy with a Scanning Tunneling Microscope," I. Appelbaum, K.J. Russell, M. Kozhevnikov, and V. Narayanamurti, *Applied Physics Letters*, **84**, No.4, 547, January 26, 2004

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

	PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.						
1.	REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE				3. DATES COVERED (From - To)		
	June 2004	Final Subcontract	Report		29 July 1999-28 September 2003		
4.	TITLE AND SUBTITLE				ITRACT NUMBER		
	Growth and Characterization of GaN As(P) for High Efficiency Solar			DE-	DE-AC36-99-GO10337		
	Cells: Final Subcontract Report, 29 July 1999–28 September 2003		5b. GRANT NUMBER				
			5c. PROGRAM ELEMENT NUMBER				
	AUTHOR/O			54 PRO IFOT NUMBER			
6.	AUTHOR(S)			5d. PROJECT NUMBER			
	V. Narayanamurti		NREL/SR-520-36318				
			5e. TASK NUMBER				
			PVP42100				
				5f WOE	5f. WORK UNIT NUMBER		
				51. WORK UNIT NUMBER			
7.	PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				8. PERFORMING ORGANIZATION		
	Harvard University				REPORT NUMBER		
	217 Pierce Hall				AAD-9-18668-17		
	Cambridge, MA 02138						
9.	SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
	National Renewable Energy Laboratory				NREL		
	1617 Cole Blvd.				11. SPONSORING/MONITORING		
	Golden, CO 80401-3393				AGENCY REPORT NUMBER		
					NREL/SR-520-36318		
12.	2. DISTRIBUTION AVAILABILITY STATEMENT						
	National Technical Information Service						
	U.S. Department of Commerce						
	5285 Port Royal Road						
	Springfield, VA 22161						
13.	3. SUPPLEMENTARY NOTES						
	NREL Technical Monitor: R. Matson						
14.	14. ABSTRACT (Maximum 200 Words)						
	This report describes the characterization of GaAs _{1-x} N _x and GaP _{1-x} N _x alloys using scanning tunneling microscopy						
	(STM) and ballistic electron emission microscopy (BEEM). One objective was to understand the origins of the giant						
	band gap bowing of these compound semiconductor alloys as a function of nitrogen concentration. The STM and						
	BEEM have been used to characterize GaN _x As _{1-x} and GaN _x P _{1-x} as a function of composition. The reduction in						
	bandgap has been measured. Detailed studies of the band structure as a function of N composition has led to a						
	basic understanding of the materials system. The major results of this work include: (i) determination of relative contributions of the Γ- and L-like bands of GaN _x As _{1-x} to the BEEM spectra; (ii) determination of the composition dependence of the Au/ G- and L-like bands of GaN _x As _{1-x} Schottky barrier height; (iii) development of a model to describe the BEEM results at nonepitaxial metal/semiconductor interfaces; and (iv) ballistic electron emission spectroscopy studies of of GaN _x P _{1-x} samples that demonstrated possible splitting in the degeneracy of the X valley						
due to the nitrogen. The data were qualitatively described by the recent perturbed host states n							
Zunger.							
15.	5. SUBJECT TERMS						
PV; scanning tunneling microscopy (STM); ballistic electron emission microscopy (BEEM); semiconductor alloys;							
bandgap; Schottky barrier; solar cells							
16.	6. SECURITY CLASSIFICATION OF: 17. LIMITATION 18. NUMBER 19a. NAME OF RESPONSIBLE PERSON						
a. REPORT b. ABSTRACT c. THIS PAGE OF ABSTRACT OF PAGES							
Unclassified Unclassified Unclassified UL 19b. TELEPONE NUMBER (Include area code)							
Ī			T				